

DG 75 AIRFLOW - INDUSTRIAL THREE PHASE



CEMENT



CERAMICS AND POTTERY INDUSTRIES



ELECTRONICS



WINE



RUBBER



- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Largest surface filter in its category
- ✓ Extractable collection container with optional use of disposable bags
- ✓ Pressure relief valve for motor protection
- ✓ Vacuum gauge to detect filter clogging
- ✓ Star-triangle switchboard
- ✓ Easy filter replacement
- ✓ Reduced downtime of machine tools
- ✓ High air flow value
- ✓ Full customization for specific needs



SUCTION UNIT

Voltage	V - Hz	400-50 3~
Power	kW	7,5
Electrical protection	IP	55
Max water lift	mmH2O	3200/2700
Max air flow	m³/h	700
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	76



FILTER UNIT

Filter Type		Star
Surface - Diameter	cm²-mm	49.500-500
Material - Efficiency	IEC 60335-2-69	Polyester - L
Air load on filter	m³/m²/h	143
Cleaning system		Manual



COLLECTION UNIT

Discharge system		Roll-out container
Capacity	lt.	100



VOLUME

Dimensions	cm	66X118X175H
Weight	kg	180



SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It is designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.

A pressure relief valve protects the motor, providing additional air for cooling.



FILTER UNIT

The large surface star filter, located inside the filter stainless steel chamber, is made of polyester and provides high resistance against clogging and passage of fine dust. It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment. The suction inlet is tangential, with an internally welded cyclone that deflects the incoming material.



COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces.

The detachable AISI 304 steel collection tank has a quick release system for the rapid disposal of the vacuumed material.



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ ANTISTATIC FILTER CLASS M
- ✓ ANTISTATIC FILTER CLASS L
- ✓ PTFE COATED FILTER CLASS M
- ✓ HEAT RESISTANT FILTER (UP TO 250° CELSIUS)
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ EARTH GROUNDING
- ✓ REMOTE CONTROL
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST



TECHNICAL

